

Issue Date 13-May-2014

Revision Date 13-May-2014

Version 1

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING****Product Name** DESOLV SF**Other means of identification****Product Code** 095**Synonyms** None**Recommended use of the chemical and restrictions on use****Recommended Use** Self-Foaming Degreaser.**Uses advised against** No information available**Manufacturer Address**

Anderson Chemical Company, 325 South Davis Avenue, Litchfield, MN 55355 (320-693-2477)

**Emergency telephone number**

Chemtrec 1-800-424-9300

**2. HAZARDS IDENTIFICATION****Classification****OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2

**Label elements****Emergency Overview****Warning****Hazard statements**

Causes skin irritation

Causes serious eye irritation

**Appearance** aqueous solution**Physical state** liquid**Odor** Solvent**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

**Precautionary Statements - Response**

Specific treatment (see Section 4 on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation occurs: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse

### **Hazards not otherwise classified (HNOC)**

#### **Other Information**

- May be harmful if swallowed
- May be harmful in contact with skin
- Harmful to aquatic life with long lasting effects

Unknown Acute Toxicity 7.2% of the mixture consists of ingredient(s) of unknown toxicity

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No.	Weight-%	Trade Secret
2-Butoxyethanol	111-76-2	12	
Dipropylene Glycol Methyl Ether	34590-94-8	5	
TSRN8300	Proprietary	0 - 10%	
TSRN2160	Proprietary	0 - 10%	

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## **4. FIRST AID MEASURES**

### **First aid measures**

<b>Eye contact</b>	Flush immediately with water for 15 minutes. Lift upper and lower eyelids for complete rinsing. Get immediate medical attention.
<b>Skin Contact</b>	Flush with water for 15 minutes. If irritation persists after rinsing, get medical attention. Remove contaminated clothing and wash before reuse.
<b>Inhalation</b>	Remove victim to fresh air. If breathing difficulty occurs or persists, get medical attention.
<b>Ingestion</b>	Rinse mouth with water. Give water to dilute. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to a semi-comatose, comatose, convulsing or unconscious person.

### **Most important symptoms and effects, both acute and delayed**

<b>Symptoms</b>	May cause moderate eye irritation which may be slow to heal. Prolonged or repeated exposure may cause skin irritation. Excessive exposure (single prolonged or repeated) may cause hemolysis (impairment of the blood to carry oxygen). Swallowing large amounts may cause injury. Excessive exposure may cause upper respiratory tract irritation.
-----------------	---

### **Indication of any immediate medical attention and special treatment needed**

<b>Note to physicians</b>	Treat symptomatically.
---------------------------	------------------------

## **5. FIRE-FIGHTING MEASURES**

### **Suitable extinguishing media**

Water spray (fog). Carbon dioxide (CO<sub>2</sub>). Dry chemical. Foam.

**Unsuitable extinguishing media** None known.

### **Specific hazards arising from the chemical**

No information available.

**Explosion data****Sensitivity to Mechanical Impact** None.**Sensitivity to Static Discharge** None.**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to cool fire exposed containers.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

<b>Personal precautions</b>	Evacuate nonessential personnel. Ventilate area. Wear appropriate personal protection equipment. Remove all sources of ignition.
<b>Environmental precautions</b>	See Section 12 for additional ecological information.
<b>Methods for containment</b>	Completely contain spilled material with dikes or sand bags, etc.
<b>Methods for cleaning up</b>	Recover as much material as possible into containers for disposal. Remaining material may be absorbed with sand, earth or vermiculite. Sweep up. Flush spill area with water.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Do not get in eyes, on skin, or clothing. Do not breathe vapors or mists. Do not ingest. Wash thoroughly after handling. Wear protective clothing/equipment. Use with adequate ventilation.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** . Keep containers tightly closed and properly labeled. This product reacts violently with bases liberating heat and causes spattering. Store in a cool, dry, well-ventilated area. Wash hands before eating, drinking, using tobacco, applying make-up or using the toilet. Do not store, use, and/or consume foods, beverages, tobacco in areas where this product is stored. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong oxidizing agents. Strong acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m <sup>3</sup>
Dipropylene Glycol Methyl Ether 34590-94-8	STEL: 150 ppm TWA: 100 ppm S*	TWA: 100 ppm TWA: 600 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 600 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 900 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 600 ppm TWA: 100 ppm TWA: 600 mg/m <sup>3</sup> STEL: 150 ppm STEL: 900 mg/m <sup>3</sup>

TSRN2160	Ceiling: 2 mg/m <sup>3</sup>	(vacated) Ceiling: 2 mg/m <sup>3</sup>	Ceiling: 2 mg/m <sup>3</sup>
----------	------------------------------	--	------------------------------

**Appropriate engineering controls**

Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Skin and body protection</b>	Natural rubber, neoprene or nitrile gloves should be worn. If contact is anticipated, wear protective clothing appropriate to use conditions.
<b>Respiratory protection</b>	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Solvent
<b>Appearance</b>	aqueous solution	<b>Odor threshold</b>	No information available
<b>Color</b>	Clear, green liquid		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	8.4	
<b>Melting point/freezing point</b>	No information available	
<b>Boiling point / boiling range</b>	No information available	
<b>Flash point</b>	> 100 °C / > 212 °F	
<b>Evaporation rate</b>	No information available	
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	No information available	
<b>Lower flammability limit:</b>	No information available	
<b>Vapor pressure</b>	No information available	
<b>Vapor density</b>	No information available	
<b>Specific Gravity</b>	1.040	
<b>Water solubility</b>	Soluble in water	
<b>Solubility in other solvents</b>	No information available	
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	No information available	
<b>Dynamic viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Density</b>	No information available
<b>Bulk density</b>	No information available

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents. Strong acids.

**Hazardous Decomposition Products**Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Aldehydes. Ketones.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information**

No data available

**Inhalation**

May cause irritation of respiratory tract.

**Eye contact**

Contact with eyes may cause irritation.

**Skin Contact**

Prolonged contact may cause redness and irritation.

**Ingestion**

Harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butoxyethanol 111-76-2	= 470 mg/kg ( Rat )	= 220 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h
Dipropylene Glycol Methyl Ether 34590-94-8	= 5230 mg/kg ( Rat )	= 9500 mg/kg ( Rabbit )	-
TSRN8300	-	> 4640 mg/kg ( Rabbit )	-
TSRN2160	= 214 mg/kg ( Rat )	-	-

**Information on toxicological effects****Symptoms**

No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Sensitization**

No information available.

**Germ cell mutagenicity**

No information available.

**Carcinogenicity**

No information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol 111-76-2	A3	Group 3	-	-

**Reproductive toxicity**

No information available.

**STOT - single exposure**

No information available.

**STOT - repeated exposure**

No information available.

**Aspiration hazard**

No information available.

**Numerical measures of toxicity - Product Information**

**Unknown Acute Toxicity** 7.2% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	2092 mg/kg
<b>ATEmix (dermal)</b>	3333 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	12.5 mg/l
<b>ATEmix (inhalation-vapor)</b>	3750 mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects

7.2% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
2-Butoxyethanol 111-76-2	-	1490: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 2950: 96 h <i>Lepomis macrochirus</i> mg/L LC50	1698 - 1940: 24 h <i>Daphnia magna</i> mg/L EC50 1000: 48 h <i>Daphnia</i> <i>magna</i> mg/L EC50
Dipropylene Glycol Methyl Ether 34590-94-8	-	10000: 96 h <i>Pimephales promelas</i> mg/L LC50 static	1919: 48 h <i>Daphnia magna</i> mg/L LC50
TSRN8300	-	100: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50	100: 48 h water flea mg/L EC50
TSRN2160	-	80: 96 h <i>Gambusia affinis</i> mg/L LC50 static	-

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

Chemical Name	Partition coefficient
2-Butoxyethanol 111-76-2	0.81
Dipropylene Glycol Methyl Ether 34590-94-8	-0.064
TSRN2160	0.65 0.83

### Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### **Contaminated packaging**

Do not reuse container.

Chemical Name	California Hazardous Waste Status
TSRN2160	Toxic Corrosive

## 14. TRANSPORT INFORMATION

### DOT

Not regulated

## 15. REGULATORY INFORMATION

### International Inventories

<b>TSCA</b>	Does not comply
<b>DSL/NDSL</b>	Does not comply
<b>EINECS/ELINCS</b>	Does not comply
<b>ENCS</b>	Does not comply
<b>IECSC</b>	Does not comply
<b>KECL</b>	Does not comply
<b>PICCS</b>	Does not comply
<b>AICS</b>	Does not comply

### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	1.0
Dipropylene Glycol Methyl Ether - 34590-94-8	1.0

#### **SARA 311/312 Hazard Categories**

<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire hazard</b>	No
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TSRN2160	1000 lb	-	-	X

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
TSRN2160	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

### US State Regulations

**California Proposition 65**

This product does not contain any Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-Butoxyethanol 111-76-2	X	X	X
Dipropylene Glycol Methyl Ether 34590-94-8	X	X	X
TSRN2160	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not Applicable

<b>16. OTHER INFORMATION</b>
------------------------------

<b>NFPA</b>	Health hazards 2	Flammability 0	Instability 0	Physical and Chemical Properties -
<b>HMIS</b>	Health hazards 2	Flammability 0	Physical hazards 0	Personal protection X

Prepared By Imt  
 Issue Date 13-May-2014  
 Revision Date 13-May-2014

Revision Note  
 No information available

**Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**