

ANDERSON CHEMICAL COMPANY  
325 South Davis Avenue  
Litchfield, MN 55355  
800-366-2477

www.ACCOMN.COM



## ANTROL COP/MANUAL CHEMICAL CONTROL UNIT

The “**ANTROL COP/MANUAL CHEMICAL CONTROL UNIT**” is a multifunctional control panel with capabilities for timed feed of **COP** or manual dispensing needs. A thorough evaluation of your equipment requirements can be supplied by your **Anderson Chemical Company** representative.

- Optional color coded push buttons allow for specific product dispensing based on industrial color code standards.
- Has the ability to operate eight air-operated pumps with accuracy and repeatability.



Antrol COP/Manual Chemical Controller

SANITATION TECHNOLOGIES

## ANTROL COP/MANUAL CHEMICAL CONTROL UNIT

Page 2

*Just The Right Chemistry.®*

### FEATURES & BENEFITS

- Smart relays allow for operation at specific times of the day and specific timing intervals.
- Independent relays allow for accurate and repeatable on/off functions.
- Regulated air pressure results from the added regulator attached.
- Colored push buttons are specific for products used in conjunction with industrial standards.
  - **Blue** for alkaline products
  - **Red** for acidic products
  - **Yellow** for chlorine and stronger oxidizing products
  - **Green** for neutral pH products
- Air-Operated Double Diaphragm pumps used for dependable product delivery.
  - Polypro available when using non-oxidizing products
  - Kynar used for specific product applications
- White Board Mounting provides a clean and sanitary appearance while providing a maintenance free environment.
- Pick up systems include ID Tags, foot valves and check valves for the prevention of siphoning, back flow and misreading of drums.
- Complete installation includes all chemical lines from drum to point of use.
- Dispensing pumps are ID Tagged for ease of reading and safety.

### CONTROL FUNCTION

- Smart relays
- Dayton timers
- Emergency stop

### SPECIFICATIONS

- 110 volt electrical power required to activate the unit
- 50 psi minimum air supply (filtered of water and oil contaminants)
- 7 scfm air volume required

### OPTIONS

- Additional manual push buttons available for added product applications
- Built-in timer allows run time to be set and adjusted easily

SINCE 1911